

# GRIP PAD®

Chipboard

# 1.2

## FRICTION

Sliding angle 44° (NF Q03-083, 1993 \* )

Grip PAD0,0054" (1.2mm) are made of dry finish chipboard 100% recycled with one or 2 sides being laminated (PVA adhesive) with Grip Sheet, a 100% recycled lightweight paper with a non slip coating.


TECHNICAL CHARACTERISTICS					
TEST	UNITS	STANDARD	NOTE *	TARGET	SPECIFICATIONS
Chipboard Thickness	mm			1,2	
Total Thickness	mm	Including Coating Height		1,3	
Chipboard Weight	g/m <sup>2</sup>			790	
Adhesive Weight	g/m <sup>2</sup>			45	
Total Weight	g/m <sup>2</sup>	Including Grip Sheet		910	
STANDARD PACKAGING					
Sheet Size	As per customer requirement, die cutting possible (round corners or other)				
Pallet Size	Typically the same size as the sheet				
Quantity per pallet	To be determined				
Stocking conditions	Dry environment				

\* Measurement has been hold in conditions of the norm NFAQ03-083, non slide side versus recycled paperboard. The friction coefficient is given as an indication. Friction properties are dependent of the surface, the weight of the product and its dimensions. Before validating the product, a test in real conditions of use is required.

## REGULATORY

- ☑ Compliant to Directive 94/62/CE
- ☑ Compliant to REACH Regulation
- ☑ Usable in food process, indirect contact

## ENVIRONMENT

- ☑ Issued of recycling fibers 
- ☑ Entirely recyclable
- ☑ Reusable
- ☑ FSC grade available on request

## HEALTH

- ☑ No toxicity
- ☑ No skin irritation